

# TM-4000 Universal Crimp Press

**The TM-4000™ Universal Crimp Press is the only industry-standard, bench-top press on the market that terminates large lug products up to 4 AWG, resulting in lower overall applied costs**

The Molex TM-4000 Universal Crimp Press provides an effective method of applying a wide range of side- and rear-feed terminals to heavy-gauge wires. The TM-4000 press is an inexpensive, electrically controlled, direct-drive press designed for midvolume, semi-automatic bench-top operations.

The industry standard TM-4000 Universal Crimp Press will accept the most common industry-standard applicators in the market place. In addition, this crimp press accepts any Molex applicator, including air-feed applicators that process terminals mounted on Mylar\* tape. This flexibility reduces tooling costs and provides production flexibility.

The Molex TM-4000 Universal Crimp Press can be used with the new Molex Tape Crimp Module (Order Number 64016-2000). This will allow crimping Molex tape-mounted terminals with the use of the current ATP-201 and ATP-301 crimping die sets. The Molex Tape Crimp Module has replaced the current Molex ATP-201 press (Order Number 19047-0001) and the Molex ATP-301 press (Order Number 19228-0030).



*TM-4000 Crimp Press with a Molex air-feed applicator that processes product on Mylar\* tape*

## FEATURES AND ADVANTAGES

Provides 3.5 metric ton-force (7000 lbf, 31 kN) of crimp force or tape-mounted terminals up to 4 AWG which lowers customer's overall applied costs

Accepts Molex FineAdjust™ and Mini-Mac™ applicators with side and rear feeds; accepts most industry-standard applicators which reduces tooling costs and provides production flexibility and increases customer quality results through the use of a consistent machine

Can be used with Molex Tape Module (64016-2000) allowing for use of current ATP-201 and ATP-301 die sets in an industry standard press to minimize customer's existing tooling investment

Shut-height adjustment cam is pre-set to industry standard 135.80mm (5.346") accepts industry-standard applicators and allows for adjustment to hit the crimp-height target

Meets OSHA safety and noise requirements and is CE approved which reduces risk of injury

TM-4000 has two safety interlock switches attached which prevent the press from cycling if guard is open or when the press is being hand cycled

## MARKETS AND APPLICATIONS


**Automotive Market**

**Industrial Market**

**Commercial Market**

**Contract Manufacturers**

**Design/Engineering Facilities**



*Molex Large 4 AWG Lug Products (supplied on Mylar tape)*



*Mini-Fit Plus HCS™ Example of a Molex terminal suited for crimping with the TM-4000*

# TM-4000 Universal Crimp Press

## SPECIFICATIONS

### Reference Information

Use With: FineAdjust™ and Mini-Mac™ applicators plus the Molex Tape Crimp Module (64016-2000)

### Electrical

240V AC/50/60Hz

### Mechanical

Air Pressure: 75.80 PSI min. (5.2 BAR)


Air Flow: 3.2 SCFM min.

Production Rate: 2,400 terminations per hour max. (dependent upon operator skill, product selection and wire length)

## UNIVERSAL PRESS QUICK REFERENCE

Order No.	Press	Voltage and Frequency	Wire Gauge	Metric ton-force
63801-7200	TM-3000™	120V AC; 50 or 60Hz	Up to 10 AWG	2
63801-7300	TM-3000™	240V AC; 50 or 60Hz	Up to 10 AWG	2
63801-7600	TM-4000™	240V AC; 50 or 60Hz	Up to 4 AWG	3.5


## IMAGE EXAMPLES OF APPLICATORS USED WITH THE TM-4000



*Air-Feed Applicator*  
Order Number: 63885-1000



*Standard Applicator*  
Order Number: 63900-2600



*Tape-Crimp Module*  
Order Number: 64016-2000

## ORDERING INFORMATION

Order No.	Use with	Largest Product Range	Used in
63801-7600	240V AC 50 or 60Hz	4 through 30 AWG	TM-4000

[www.molex.com/link/tm4000.html](http://www.molex.com/link/tm4000.html)